RMV-55-ZXX and RM-55

Product Features

- Variable Zeppelin
- Variable Venturi
- Various Zeppelin sizes available
- Accurate gas metering
- Fast response to load transient
- CAN Communication
- Automatic and Manual drive
- RM-55/RMV-55 40 to 60 litre engine displacement
- Status indication as position feedback

Advantage

- 12 and 24 VDC
- IP-67 Protected
- High temperature real contactless position feedback
- Variable Geometry
- Controllable, via: CAN, 0-10 VDC or 4-20mAmp
- Mounting flange for gas tube is removable for easy external mounting and service
- Has two mounting flanges
- Zeppelin can be swapped without removing the mixer from the engine

WITH VARIABLE VENTURI-GEOMETRY



Precise air gas metering

The RMV Mixer is an enhanced sophisticated Air Gas blender based on the approved ring gap principal.

Due to a precise HT-mechanical gear system an accurate Lambda control tolerance smaller than +/- 0.01 is guaranteed.

It can be used for different type of engines. Via CAN, 0-10VDC or 4-20mAmp the mixer can be easily controlled. In combination with the Cuteline Mixer Module it unleashes a powerful way of controlling the air fuel ratio.


Engineering and design has achieved a level which allows using the mixer for Natural, Bio and other gas application. Robustness and environmental protection makes this mixer unique and extremely user friendly.


CAN Bus communication allows flexibility together with HT Genset Controller and CuteLine series control system and cost savings for additional I/O's.




1

Dimensions RM-55 RMV-55 Series







Mating Harness for RM-55:

CH-RM-LX (X= Define length) Normally 4 or 7 meter available otherwise specify length.

If CL Mixer Version is used:


Appropriate Driver Module: No additional driver required, can be driven directly with below mentioned modules.

Appropriate Air Fuel Ratio Controller: HT-CL-AF-1000LS or HT-CL-AF-1500P



Mixer Assembly

RMV-55 Series






Gas Mixer

3-D View RM-55 Series









4

Dimensions RMV-55-ZXX





Mating Harness for RMV-55-ZXX:


CH-RMV-Z-LX (X= Define length) Normally 4 or 7 meter available otherwise specify length.


Appropriate Driver Module: HT-CL-MIXRMV, controls both motors.

Appropriate Air Fuel Ratio Controller: HT-CL-AF-1000LS or HT-CL-AF-1500P

Zeppelin diameter 65mm. Other diameter available.







Local Distributor / Partner:

