

## Environmentally Sealed Bus Bar

### Product Features

- 100% sealed connections
- Up to 24 individual connections to the bus
- Up to 60A current capability
- Short circuit and over load protection
- Small footprint
- Potted - true IP67 rating
- Easy 2 point mounting / rugged ABS housing
- Customizable



## Environmentally Sealed Bus Bar

This module eliminates corroded connection points and the potential for intermittent connections on the bus bar. All connections utilize Deutsch sealed automotive connectors to provide up to a 60A bus connection point in extreme duty conditions.

### Unit Connections

Input connector	.....	DTHD04-1-8P
Mate connector	.....	DTHD06-1-8S
Mate contact	.....	0462-203-08141
Bus connections	.....	DTF15-12PA
Mate connector	.....	DT06-12SA
Mate contact	.....	0462-201-16141
Mate wedge lock	.....	W12S

### Specifications

Current capacity	.....	60A Max
Current per pin	.....	13.0A Max
Storage temperature	.....	-40° to 85° C
Operating temperature	.....	-40° to 85° C
IP rating	.....	67
Weight	.....	0.30 lbs. Typ
Dimensions	.....	2.000" W x 3.125" L x 2.313" H
Mounting holes (2)	.....	3.500" apart, 0.188" Dia.



HUEGLI TECH AG (LTD)  
Murgenthalstrasse 30  
4900 Langenthal Switzerland  
Phone: +41 62 916 50 30  
Fax: +41 62 916 50 35

e-mail: [sales@huegli-tech.com](mailto:sales@huegli-tech.com)  
[www.huegli-tech.com](http://www.huegli-tech.com)