

HT-CL-BOUT8

Common features

- 8 configurable outputs
- communication by CAN bus (supports div. protocols)
- communication by Modbus RTU RS485
- power supply 7-30 VDC
- -40°C - +85°C
- DIN Rail 35mm



CuteLine Binary Output Module

A universal usable output module to expand a gen-set controller by 8 binary outputs.

When the main controller does not have enough inputs and outputs you can expand them by adding a CuteLine module.

By using of the regular configuration software you simply add and embed it into your control system.

With the communication options of CAN bus and Modbus RTU the connection to the main controller is very simple.

Technical Data

Power Supply	7-30VDC, Reverse Polarity Protected
Current Consumption.....	45mA with 24VDC Input @ 25°C(Output Fully Off State)
Number of Outputs.....	8, Configurable, Non-Isolated, Short-Circuit Protected
Output Current Rating.....	Maximum 0.5A Per Channel
On/Off State Voltage Drop.....	0.2Vdc Maximum
Output Signal Delay.....	Off to On State @ 10mS Maximum
.....	On to Off State @ 10mS Maximum
Communication Supported Protocols.....	Can Bus IS/IG
.....	Can Bus HT Controller
.....	Mod Bus RTU
Operational Temperature.....	-40 to +85 oC (-40 to +185oF)
Storage Temperature.....	-40 to +85 oC (-40 to +185oF)
Relative Humidity.....	5 to 95%, Non-condensing
Dimension (including terminal blocks).....	30 x 110 x 94 mm
Weight (including terminal blocks).....	190g
Wire Size.....	22 to 12 AWG
Mounting.....	DIN Rail 35 mm

Order codes

- HT-CL-AINT01-00Analogue input temp module
- HT-CL-AINU01-00.....Analogue input volt/curr module
- HT-CL-AOUT01-00.....Analogue output volt/curr module
- HT-CL-BIN01-00.....Binary input module
- HT-CL-BOUT01-00.....Binary output module



Local Distributor / Partner:



HUEGLI TECH AG (LTD)
Murgenthalstrasse 30
4900 Langenthal Switzerland
Phone: +41 62 916 50 30
Fax: +41 62 916 50 35

e-mail: sales@huegli-tech.com
www.huegli-tech.com